



MDF 82

Power Strip

- **MDF 82** is a power strip 220V with 8 IEC filtered by RF and VDR filters to suppress impulsive disturbances from the mains. The management system of the power supplies is of fundamental importance when you have to turn on multiple devices at same time.
- **MDF 82** is manufactured according 19" standard rack and is equipped with an integrate anti-pump circuit to eliminate the annoying "PUMP" switching on and off of some amplification system.
- **MDF 82** is recommended for its ease of use and its absolute security. In case of doubts on the power supply system it is necessary to use it, otherwise failures in the system itself may occur.
- **MDF 82** brilliantly solves every need of the power management.



TECHNICAL CHARACTERISTICS

- DESCRIPTION: _____ 220 V strip
- ANTI-PUMP CIRCUIT: _____ insertable
- PROTECTION: _____ RF - VDR
- VAC MAIN: _____ 230 V - 50 Hz
- VAC OUT: _____ 230 V - 50 Hz
- AC OUTPUTS: _____ 8 x 230 V
- APPEARANCE: _____ 1U standard rack
- DIMENSIONS (WxHxD): _____ mm 483 x 45 x 310
- WEIGHT: _____ Kg 3,5



UP 1x120

Amplifier

Power amplifier 1x120 W RMS for professional audio, with output transformer 8 Ohm 4 Ohm, 50/100V.

XLR input and Euroblock output connections.

UP series is designed for a wide variety of applications: churches, multi-functional meeting rooms, auditoriums, open spaces and various places of worship.

This amplifier provides ample power for loudspeaker systems for sound reinforcement distributed with a high number of fixed impedance or high impedance speakers.

THD performance (signal-noise ratio) with 0.1% ratio at 100dB. All Fulgor Service power units and amplifiers have professional performance while keeping THD as low as possible to achieve outstanding quality that has always distinguished them.

UP 1X120 power amp requires no internal fans for cooling. The latter is carried out by a heat sink that ensures excellent heat exchange in a silent and reliable way.

UP 1x120 has electronic circuitry with quality and safety features.

The metal carpentry is suitable for flat support and is designed for 19" rack mounting (1 rack unit).



TECHNICAL CHARACTERISTICS

UP 1 X 120

- DESCRIPTION: _____ 1 channel amplifier
- RATED MAXIMUM POWER: _____ 1 x 120 W
- PEAK POWER: _____ 1 x 180 W
- VOLUME CONTROL: _____ frontal potentiometers
- COOLING: _____ air cooling by dissipator
- LINE IN: _____ balanced XLR
- OUTPUT TRANSFORMER: _____ Ohm / Volt
- PASSBAND: _____ 20-22.000 Hz ± 2 dB
- DIMENSIONS (WxHxD): _____ mm 483 x 44 x 275
- WEIGHT: _____ Kg 6

The images are purely illustrative and the details can be changed without any warning.